



Document Title	HSD150SXA1-A Tentative Specification	Page No.	1 / 30
Document No.		Revision	1.0

To :

Date :

HannStar Product Specification **Tentative**

Model : HSD150SXA1-A

- Note :
1. The information contained herein is preliminary and may be changed without prior notices.
 2. Please contact HannStar Display Corp. before designing your product based on this module specification.
 3. The information contained herein is presented merely to indicate the characteristics and performance of our products. No responsibility is assumed by HannStar for any intellectual property claims or other problems that may result from application based on the module described herein.

Document Title	HSD150SXA1-A Tentative Specification	Page No.	2 / 30
Document No.		Revision	1.0

Record of Revisions

Rev.	Updated No.	Date	Description of change
1.0	---	July.01, 2002	Tentative specification for HSD150SXA1-A was first issued.



Document Title	HSD150SXA1-A Tentative Specification	Page No.	3 / 30
Document No.		Revision	1.0

Contents

1.0	General descriptions	p.4
2.0	Absolute maximum ratings	p.5
3.0	Optical characteristics	p.7
4.0	Block diagram	p.12
5.0	I/O Connection Pin assignment	p.15
6.0	Electrical Characteristics.....	p.17
7.0	Outline dimension	p.26
8.0	Lot Mark	p.28
9.0	General precaution	p.29

Document Title	HSD150SXA1-A Tentative Specification	Page No.	4 / 30
Document No.		Revision	1.0

1.0 GENERAL DESCRIPTIONS

1.1 Introduction

HannStar Display model **HSD150SXA1-A** is a color active matrix thin film transistor (TFT) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching device. This model is composed of a TFT LCD panel, the voltage reference, common voltage, DC-DC converter, column, and row driver circuit. This TFT LCD has a 15-inch diagonally measured active display area with XGA resolution (768 vertical by 1024 horizontal pixel array).

1.2 Features

- 15" XGA TFT LCD panel
- 2 CCFLs Backlight system
- RSDS, 1 pixel/clock
- Supported XGA (V:768 lines, H:1024 pixels) resolution
- Supported to 75Hz refresh rate
- Without LCD Timing Controller

1.3 General information

Item	Specification	Unit
Outline dimension	326.0 × 249.0 × 10.2 (Max.) with 2 brackets	mm
Display area	304.1(H) x 228.1(V) (15.0" diagonal)	mm
Number of Pixel	1024(H) x 768(V)	pixels
Pixel pitch	0.297(H) x 0.297(V)	mm
Pixel arrangement	RGB Vertical stripe	
Display color	6-bits driver with RSDS I/F	
Display mode	Normally white	
Surface treatment	Antiglare, Hard-Coating (3H)	
Weight	1000 (Max.)	g
Back-light	2-CCFLs, Top & bottom edge side	
Input signal	Source and Gate Driver control signals	
Power consumption	11 W (Typ.), with back light	W
Optimum viewing direction	6 o'clock	

1.4 Applications

- Desktop monitors
- Display terminals for AV applications
- Monitors for industrial applications

Document Title	HSD150SXA1-A Tentative Specification	Page No.	5 / 30
Document No.		Revision	1.0

1.5 Mechanical Information

Item		Min.	Typ.	Max.	Unit
Module Size	Horizontal(H)	-	326.0	-	mm
	Vertical(V)	-	249.0	-	mm
	Depth(D)	-	9.9	10.2	mm
Weight (without inverter)		-	960	1000	g

Notes: **HannStar added 2 brackets to extend to 326.0 horizontal outlines.**


2.0 ABSOLUTE MAXIMUM RATINGS

2.1 Absolute Rating of Environment

Item	Symbol	Min.	Max.	Unit	Note
Storage temperature	T _{STG}	-20	60	°C	
Operating temperature	T _{OPR}	0	50	°C	
Vibration (non-operating)	V _{NOP}	--	1.5	G	(1)
Shock (non-operating)	S _{NOP}	--	70	G	(2)
Storage humidity	H _{STG}	10	90	%RH	(3)
Operating humidity	H _{OP}	10	80	%RH	(3)
Low pressure (operating)	P _{LOP}	697	--	HPa	(4)
Low pressure (non-operating)	P _{LNOP}	116	--	HPa	(5)

- Note
- (1) 5-500Hz sine wave, X,Y,Z each directions, 30 min/cycle.
 - (2) 11ms, $\pm X$, $\pm Y$, $\pm Z$ direction, one time each. For this shock test, it is necessary to fill the silicon rubber between the shock jig as buffer.
 - (3) Max wet bulb temp. =39°C
 - (4) 2 hrs. (10000 feet)
 - (5) 24hrs. (50000 feet)

Document Title	HSD150SXA1-A Tentative Specification	Page No.	6 / 30
Document No.		Revision	1.0



2.2 Electrical Absolute Rating:

2.2.1 TFT LCD Module:

Item	Symbol	Condition	Value		Unit
			min.	max.	
Input Power Voltage 1	V_{DD1}	Normal	+3.0	+3.8	V(DC)
Logic Signal input voltage	V_{SIG}	Normal	-0.3	$V_{DD1} + 0.3$	V
Input Power Voltage 2	V_{DD2}	Normal	+10.0	+14.0	V(DC)

2.2.2 Back Light Unit:

Item	Symbol	Min.	Max.	Unit	Note
Lamp voltage	V_L	0	2000	V(rms)	(1)
Lamp current	I_L	—	7.0	mA	(1)
Lamp frequency	f_L	0	100	KHz	(1)

Note: (1) Permanent damage may occur to the LCD module if beyond this specification.
Functional operation should be restricted to the conditions described under Normal Operating Conditions.

Document Title	HSD150SXA1-A Tentative Specification	Page No.	7 / 30
Document No.		Revision	1.0

3.0 OPTICAL CHARACTERISTICS

3.1 Measuring Condition

- Measuring surrounding: dark room
- Lamp current I_{BL} : **(6.0)±0.1mA**, lamp freq. F_L =50KHz
- V_{DD1} =3.3V, f_V =60Hz, f_{DCLK} =32.5MHz
- Surrounding temperature: 25±2°C. 30min. Warm-up time.

3.2 Measuring Equipment


- LCD-7000 of Otsuka Electric Corp., which utilized MCPD-7000 for Chromaticity and BM-5A for other optical characteristics.
- Measuring spot size: 10~12mm

3.3 Optical specification

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note	
Contrast		CR	$\Theta=0^{\circ}$ $\phi=0^{\circ}$ Normal viewing angle	300	400	--		(1)(2)	
Response time	Rising	T _R		--	TR +TF =(35)	--	msec	(1)(3)	
	Falling	T _F		--		--			
White luminance (center of		Y _L		--	250	--	cd/m ²	(1)	
Color chromaticity (CIE1931)	Red	R _x		$\phi=0^{\circ}$ Normal viewing angle	0.597	0.627	0.657		(1)(4)
		R _y			0.308	0.338	0.368		
	Green	G _x			0.266	0.296	0.326		
		G _y			0.566	0.596	0.626		
	Blue	B _x			0.119	0.149	0.179		
		B _y			0.086	0.116	0.146		
	White	W _x	0.285		0.315	0.345			
		W _y	0.303		0.333	0.363			
Viewing angle	Hor.	Θ _L	CR>10	--	65	--			
		Θ _R		--	65	--			
	Ver.	Θ _H		--	45	--			
		Θ _L		--	55	--			
Brightness uniformity		B _{UNI}	$\Theta=0^{\circ}$ $\phi=0^{\circ}$	75	80	--	%	(5)	
Gamma value				--	--	--	%	(6)	
Cross talk		CT(n)		--	--	1.2		(7)	
Image sticking		2hrs				5	sec	(8)	
Luminance uniformity (TCO'99)		L _R				1.7		(9)	

Document Title	HSD150SXA1-A Tentative Specification	Page No.	8 / 30
Document No.		Revision	1.0

Note (1) Definition of Viewing Angle:




Note (2) Definition of Contrast Ratio(CR) :
measured at the center point of panel


$$CR = \frac{\text{Luminance with all pixels white (L63)}}{\text{Luminance with all pixels black (L0)}}$$

Document Title	HSD150SXA1-A Tentative Specification	Page No.	9 / 30
Document No.		Revision	1.0

Note (3) Definition of Response Time: Sum of T_R and T_F




Note (4) Optical characteristic measurement setup



Document Title	HSD150SXA1-A Tentative Specification	Page No.	10 / 30
Document No.		Revision	1.0

Note (5) Definition of brightness uniformity

Luminance uniformity =(Min Luminance)/(Max Luminance) x 100%



Note (6) Gamma values shall be measured at the center location.

n	Gs(S)	Relative Brightness (%)			Remark
		Min.	Typical	Max.	
0	0	-	0.2	-	
1	31	-	0.7	-	
2	63	-	4.0	-	
3	95	-	11.0	-	
4	127	-	19.0	-	
5	159	-	34.0	-	
6	191	-	54.0	-	
7	223	-	75.0	-	
8	255	-	100.0	-	

Document Title	HSD150SXA1-A Tentative Specification	Page No.	11 / 30
Document No.		Revision	1.0

Note (7) Definition of crosstalk CT (1) ~ CT (4)

$$CT(n) = \frac{|L(n) - LB(n)|}{L(n)} \times 100\%, n = 1 \sim 4$$


Where L(n) = Luminance of point "n" at pattern A (cd/m²) , n=1~4

LB(n) = Luminance of point "n" at pattern B (cd/m²) , n=1~4

The location measured will be exactly the same in both patterns.

L0: Luminance with all pixels black

L63: Luminance with all pixels white



Note (8) Image sticking specifications as follows:

After 2 hours on condition of fixed patterns at 50°C and 90%RH ,it does not remain in 5 seconds on the full white pattern.


Note (9) TCO99 Certification Requirements and test methods for environmental labeling of Displays [Flat] Report No.2 (X1.5.2 Luminance Uniformity)

$$L_R = ((L_{\max,+30\deg} / L_{\min,+30\deg}) + (L_{\max,-30\deg} / L_{\min,-30\deg})) / 2$$

Document Title	HSD150SXA1-A Tentative Specification	Page No.	12 / 30
Document No.		Revision	1.0


4.0 BLOCK DIAGRAM

4.1 LCD Module Block Diagram:



Document Title	HSD150SXA1-A Tentative Specification	Page No.	13 / 30
Document No.		Revision	1.0

4.2 Pixel Format



Document Title	HSD150SXA1-A Tentative Specification	Page No.	14 / 30
Document No.		Revision	1.0

4.3 Relationship between Displayed Color and Input Data

	Display	MSB R5 R4 R3 R2 R1 R0						LSB G5 G4 G3 G2 G1 G0						MSB B5 B4 B3 B2 B1 B0						Gray scale level
Basic color	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	-
	Blue	L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	H	-
	Green	L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	H	-
	Light Blue	L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	H	-
	Red	H	H	H	H	H	H	L	L	L	L	L	L	L	L	L	L	L	L	-
	Purple	H	H	H	H	H	H	L	L	L	L	L	L	H	H	H	H	H	H	-
	Yellow	H	H	H	H	H	H	H	H	H	H	H	H	L	L	L	L	L	L	-
	White	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	-
Gray scale of Red	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0
	Dark ↑ ↓ Light	L	L	L	L	L	H	L	L	L	L	L	L	L	L	L	L	L	L	L1
		L	L	L	L	H	L	L	L	L	L	L	L	L	L	L	L	L	L	L2
		:						:						:						L3...L60
		:						:						:						L61
		H	H	H	H	L	H	L	L	L	L	L	L	L	L	L	L	L	L	L62
	Red	H	H	H	H	H	H	L	L	L	L	L	L	L	L	L	L	L	L	Red L63
Gray scale of Green	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0
	Dark ↑ ↓ Light	L	L	L	L	L	L	L	L	L	L	L	H	L	L	L	L	L	L	L1
		L	L	L	L	L	L	L	L	L	L	H	L	L	L	L	L	L	L	L2
		:						:						:						L3...L60
		:						:						:						L61
		L	L	L	L	L	L	H	H	H	H	L	H	L	L	L	L	L	L	L62
	Green	L	L	L	L	L	L	H	H	H	H	H	H	L	L	L	L	L	L	Green L63
Gray scale of Blue	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0
	Dark ↑ ↓ Light	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	H	L1
		L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	H	L	L2
		:						:						:						L3...L60
		:						:						:						L61
		L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	L	H	L62
	Blue	L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	H	Blue L63
Gray scale of White and Black	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0
	Dark ↑ ↓ Light	L	L	L	L	L	H	L	L	L	L	L	H	L	L	L	L	L	H	L1
		L	L	L	L	H	L	L	L	L	L	H	L	L	L	L	L	H	L	L2
		:						:						:						L3...L60
		:						:						:						L61
		H	H	H	H	L	H	H	H	H	L	H	H	H	H	H	L	H	L	L62
	White	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	White L63

Document Title	HSD150SXA1-A Tentative Specification	Page No.	15 / 30
Document No.		Revision	1.0


5.0 I/O CONNECTION PIN ASSIGNMENT

5.1 Interface FPC Connector CN1 (50-pins x 1) (HannStar Electrical Corp.)

I/F FRC Connector CN1		
Pin No.	Symbol	Description
1	GND	Ground
2	D22P	RSDS Receiver Data + (Blue)
3	D22N	RSDS Receiver Data - (Blue)
4	GND	Ground
5	D21P	RSDS Receiver Data + (Blue)
6	D21N	RSDS Receiver Data - (Blue)
7	GND	Ground
8	D20P	RSDS Receiver Data + (Blue)
9	D20N	RSDS Receiver Data - (Blue)
10	GND	Ground
11	D12P	RSDS Receiver Data + (Green)
12	D12N	RSDS Receiver Data - (Green)
13	GND	Ground
14	D11P	RSDS Receiver Data + (Green)
15	D11N	RSDS Receiver Data - (Green)
16	GND	Ground
17	D10P	RSDS Receiver Data + (Green)
18	D10N	RSDS Receiver Data - (Green)
19	GND	Ground
20	CLKP	RSDS Receiver clk +
21	CLKN	RSDS Receiver clk -
22	GND	Ground
23	D02P	RSDS Receiver Data + (Red)
24	D02N	RSDS Receiver Data - (Red)
25	GND	Ground
26	D01P	RSDS Receiver Data + (Red)
27	D01N	RSDS Receiver Data - (Red)
28	GND	Ground
29	D00P	RSDS Receiver Data + (Red)
30	D00N	RSDS Receiver Data - (Red)
31	GND	Ground
32	STH	Start pulse I/O
33	LOAD	CK1
34	POL	Odd & Even change
35	REV	Data polarity inversion
36	GND	Ground
37	CPV	Vertical shift clock input
38	STV	Shift data I/O
39	OE	Output enable pin
40	NC	
41	GND	Ground
42	VDD1	3.3V Power Input
43	VDD1	3.3V Power Input
44	VDD1	3.3V Power Input
45	GND	Ground
46	VDD2	12V Power Input
47	VDD2	12V Power Input
48	ID1	Panel ID (Reserve pin)
49	ID2	Panel ID (Reserve pin)
50	ID3	Panel ID (Reserve pin)

Document Title	HSD150SXA1-A Tentative Specification	Page No.	16 / 30
Document No.		Revision	1.0

5.2 Back Light Unit (CCFL) Connectors:



CN2, 3: CCFL Power Source (BHR-03VS-1/Japan Solderless Terminal MFG Co., LTD)

Mating connector: SM02 (8.0)B-BHS-1/ Japan Solderless Terminal MFG Co., LTD

Terminal No.	Symbol	Function
1	VL	CCFL power supply (high voltage)
2	NC ¹⁾	No connection
3	GL	CCFL power supply (low voltage)

Note 1) Please connects NC pin to nothing. Don't connect it to ground nor to other signal Input. (NC pin should be open.)

Document Title	HSD150SXA1-A Tentative Specification	Page No.	17 / 30
Document No.		Revision	1.0

6.0 ELECTRICAL CHARACTERISTICS

6.1 Electrical System of LCD Module:

Item	Symbol	Condition	Value			Unit
			Min.	Typ.	Max.	
Input Voltage	V_{DD1}		+3.0	+3.3	+3.6	V(DC)
	V_{DD2}		+11.0	+12.0	+13.0	
Input Rush Current	I_{rush}	$V_{DD1} = +3.3V$			0.5	A
		$V_{DD2} = +12.0V$			1.0	
Input Signal voltage	V_{IH}	High Level	2.4	3.3	$V_{DD1}+0.2$	V
	V_{IL}	Low Level	0	—	0.9	V


6.2 Back-Light Unit:

The backlight system is an edge-lighting type with 2-CCFL (Cold Cathode Fluorescent Lamp). The characteristics of four lamps are shown in the following tables.

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Lamp current	I_L	3.0	6.0	7.0	mA(rms)	(1)
Lamp voltage	V_L	630	700	770	V(rms)	$I_L=6.0$ mA
Frequency	f_L	50	55	80	KHz	(2)
Operating life time	Hr	30,000	—	—	Hour	(3)
Startup voltage	V_s	1150	—	—	V(rms)	at 25°C
		1350				at 0°C

Document Title	HSD150SXA1-A Tentative Specification	Page No.	18 / 30
Document No.		Revision	1.0

Note: (1) Lamp current is measured with current meter for high frequency as shown below. Specified values are for a lamp.



- (2) Lamp frequency may produce interference with horizontal synchronous frequency and this may cause line flow on the display. Therefore lamp frequency shall be detached from the horizontal synchronous frequency and its harmonics as far as possible in order to avoid interference.
- (3) Life time (Hr) can be defined as the time in which it continues to operate under the condition: Temp. = $25 \pm 3^{\circ}\text{C}$, $I_L = 6.0\text{mA(rms.)}$ and $f_L = 50\text{ KHz}$ until one of the following event occurs:
1. When the brightness becomes 50%.
 2. When the startup voltage (V_s) at 0°C becomes higher than the maximal value of V_s specified above.

Document Title	HSD150SXA1-A Tentative Specification	Page No.	19 / 30
Document No.		Revision	1.0

6.3 AC Electrical Characteristics:

6.3.1 AC Timing: (VDD1=3.0V~3.6V, T_{OPR}=25 °C)⁵⁾

Item	Symbol	Min.	Typ.	Max.	Unit	Signals	Note
Reference Signal (Pixel Clock)	F1 T1=CLK T2=T1*2	50 12.5 25	65 15.384 30.769	80 20 40	MHz n-Sec n-Sec		
Reference Signal (DENB)	Line Periodic	T3=Line	526	672	900	T2	
	Line Active	T4	512	512	512	T2	
	Line Blank	T5	14	160	388	T2	
	Frame Periodic	T6	773	806	950	Lines	
	Frame Active	T7	768	768	768	Lines	
	Frame Blank	T8	5	---	---	Lines	
Vertical Periodic	Periodic	T6	773	806	950	Lines	
	Pulse Width	T9	1	1	---	Lines	
	Rising Time	T11	---	40	60	n-Sec	
	Falling Time	T12	---	40	60	n-Sec	
	Set-up Time	T13	700	800	---	n-Sec	
	Hold Time	T14	700	800	---	n-Sec	
Horizontal Periodic	Period	T15	---	1	---	Lines	
	Pulse Width	T16A	1			u-Sec	
		T16B	1			u-Sec	
		T16C	2	64	100	T2	
	Rising Time	T17A		40	60		
		T17B		40	60	n-Sec	
		T17C	2	4			
	Falling Time	T18A		40	60		
		T18B		40	60	n-Sec	
		T18C	2	4			

Document Title	HSD150SXA1-A Tentative Specification	Page No.	20 / 30
Document No.		Revision	1.0

Item	Symbol	Min.	Typ.	Max.	Unit	Signals	Note
Clock	Pulse width	T19	15	---	---	n-Sec	CLKP- CLKN
	Pulse low period	T19A	6	---	---	n-Sec	
	Pulse high period	T19B	6	---	---	n-Sec	
Start pulse	Data setup time	T20	2	---	---	n-Sec	STH
	Data hold time	T21	1	---	---	n-Sec	
	Setup time	T22	4	---	---	n-Sec	
	Hold time	T23	2	---	---	n-Sec	
	Signal pulse width	T24	1CLKP	---	2CLKP	n-Sec	
Load	Load high pulse width	T25	5CLKP	---	2 μ s	CLKP period	LOAD
	Load to STH setup time	T26	5CLKP	---	---	CLKP period	
	Last data time	T27	1CLKP	---	---	CLKP period	
	Load(rising)~ Load(falling)	T28	4	---	---	n-Sec	
	POL(rising) or (falling) ~ Load(rising)	T29	14	---	---	n-Sec	
	Load(falling)~ POL(rising)or (falling)	T30	10	---	---	n-Sec	

Note 1) Refer to VESA standard.


Note 2) Please adjust LCD operating signal timing and FL driving frequency, to optimize the display quality. There is a possibility that flicker is observed by the interference of LCD operating signal timing and FL driving condition (especially driving frequency).

Note 3) All the timing setting should be confirmed with HannStar's FAE persons.

Document Title	HSD150SXA1-A Tentative Specification	Page No.	21 / 30
Document No.		Revision	1.0


6.3.2 AC Timing Charts:

(1). Reference Signal (pixel clock):




Document Title	HSD150SXA1-A Tentative Specification	Page No.	22 / 30
Document No.		Revision	1.0

(2). Vertical Periodic (STV, OE, CPV):




Document Title	HSD150SXA1-A Tentative Specification	Page No.	23 / 30
Document No.		Revision	1.0

(3). Horizontal Periodic 1 (STH, CLK, DATA):




Document Title	HSD150SXA1-A Tentative Specification	Page No.	24 / 30
Document No.		Revision	1.0

(4). Horizontal Periodic 2 (CLK, LOAD, STH, POL):



Document Title	HSD150SXA1-A Tentative Specification	Page No.	25 / 30
Document No.		Revision	1.0

6.4 Power On / Off Sequence :



Item	Min.	Typ.	Max.	Unit	Remark
TP1	20	--	--	msec	
TP2	20	--	--	msec	
TP3	0	--	10	msec	
TP4	0	--	10	msec	
TP5	0	--	50	msec	
TP6	0	--	50	msec	
TP7	200	--	--	msec	
TP8	200	--	--	msec	
TP9	1	--	--	sec	


- Note : (1) The supply voltage of the external system for the module input should be the same as the definition of V_{DD} .
- (2) Apply the lamp voltage within the LCD operation range. When the back-light turns on before the LCD operation or the LCD turns off before the back-light turns off, the display may momentarily become white.
- (3) In case of $V_{DD} = \text{off level}$, please keep the level of input signal on the low or keep a high impedance.
- (4) TP9 should be measured after the module has been fully discharged between power off and on period.
- (5) Interface signal shall not be kept at high impedance when the power is on.

Document Title	HSD150SXA1-A Tentative Specification	Page No.	26 / 30
Document No.		Revision	1.0

7.0 OUTLINE DIMENSION

7.1.1 Front View:


Date: 20020315



Document Title	HSD150SXA1-A Tentative Specification	Page No.	27 / 30
Document No.		Revision	1.0

7.1.2 Back View:

Date: 20020315



Document Title	HSD150SXA1-A Tentative Specification	Page No.	28 / 30
Document No.		Revision	1.0

8. LOT MARK

8.1 Lot Mark

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----

code 1,2,3,4,5,6: HannStar internal flow control code.

code 7: production location.

code 8: production year.

code 9: production month.

code 10,11,12,13,14,15: serial number.

Note (1) Production Year

Year	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008
Mark	9	0	1	2	3	4	5	6	7	8

Note (2) Production Month

Month	Jan.	Feb.	Mar.	Apr.	May.	Jun.	Jul.	Aug.	Sep.	Oct	Nov.	Dec.
Mark	1	2	3	4	5	6	7	8	9	A	B	C


8.2 Location of Lot Mark

(1) The label is attached to the backside of the LCD module.

(2) This is subject to change without prior notice.



Lot mark



Document Title	HSD150SXA1-A Tentative Specification	Page No.	29 / 30
Document No.		Revision	1.0

9.0 GENERAL PRECAUTION

9.1 Use Restriction

This product is not authorized for use in life supporting systems, aircraft navigation control systems, military systems and any other application where performance failure could be life-threatening or otherwise catastrophic.

9.2 Disassembling or Modification

Do not disassemble or modify the module. It may damage sensitive parts inside LCD module, and may cause scratches or dust on the display. HannStar does not warrant the module, if customers disassemble or modify the module.

9.3 Breakage of LCD Panel

- 9.3.1 If LCD panel is broken and liquid crystal spills out, do not ingest or inhale liquid crystal, and do not contact liquid crystal with skin.
- 9.3.2 If liquid crystal contacts mouth or eyes, rinse out with water immediately.
- 9.3.3 If liquid crystal contacts skin or cloths, wash it off immediately with alcohol and rinse thoroughly with water.
- 9.3.4 Handle carefully with chips of glass that may cause injury, when the glass is broken.

9.4 Electric Shock

- 9.4.1 Disconnect power supply before handling LCD module.
- 9.4.2 Do not pull or fold the CCFL cable.
- 9.4.3 Do not touch the parts inside LCD modules and the fluorescent lamp's connector or cables in order to prevent electric shock.

9.5 Absolute Maximum Ratings and Power Protection Circuit

- 9.5.1 Do not exceed the absolute maximum rating values, such as the supply voltage variation, input voltage variation, variation in parts' parameters, environmental temperature, etc., otherwise LCD module may be damaged.
- 9.5.2 Please do not leave LCD module in the environment of high humidity and high temperature for a long time.
- 9.5.3 It's recommended employing protection circuit for power supply.

9.6 Operation

- 9.6.1 Do not touch, push or rub the polarizer with anything harder than HB pencil lead.
- 9.6.2 Use fingerstalls of soft gloves in order to keep clean display quality, when persons handle the LCD module for incoming inspection or assembly.
- 9.6.3 When the surface is dusty, please wipe gently with absorbent cotton or other soft material.
- 9.6.4 Wipe off saliva or water drops as soon as possible. If saliva or water drops contact with polarizer for a long time, they may causes deformation or color fading.
- 9.6.5 When cleaning the adhesives, please use absorbent cotton wetted with a little petroleum benzine or other adequate solvent.

Document Title	HSD150SXA1-A Tentative Specification	Page No.	30 / 30
Document No.		Revision	1.0

9.7 Mechanism

Please mount LCD module by using mounting holes arranged in four corners tightly.

9.8 Static Electricity

- 9.8.1 Protection film must remove very slowly from the surface of LCD module to prevent from electrostatic occurrence.
- 9.8.2 Because LCD module uses CMOS-IC on circuit board and TFT-LCD panel, it is very weak to electrostatic discharge. Please be careful with electrostatic discharge.
- 9.8.3 Persons who handle the module should be grounded through adequate methods.

9.9 Strong Light Exposure

The module shall not be exposed under strong light such as direct sunlight. Otherwise, display characteristics may be changed.

9.10 Disposal

When disposing LCD module, obey the local environmental regulations.